

DIRECT BURIAL SPEAKER CABLE - SHIELDED AND UNSHIELDED
 12 TO 22 AWG 2C TO 8C STRANDED BC

1/6/2005 REV. 0



CONDUCTORS: STRANDED BARE COPPER
INSULATION: PVC
SHIELD: ALUMINUM POLYMER
JACKET: SUNLIGHT-RESISTANT PVC
TEMPERATURE RATING: -20 TO +75 DEG C
OPERATING VOLTAGE: 300V
UL TYPE OR STYLE: DIRECT BURIAL

COLOR CODE CHART:

CONDUCTOR	COLOR	CONDUCTOR	COLOR
1ST	BLACK	5TH	YELLOW
2ND	RED	6TH	BROWN
3RD	BLUE	7TH	RED
4TH	ORANGE	8TH	BLUE/BLACK

PART NO	AWG	NUMBER OF CONDUCTORS	STRAND	NOM INSULATION THICKNESS (INCHES)	NOM JACKET THICKNESS (INCHES)	NOM OD (INCHES)	WEIGHT (LBS.) PER 1000'	JACKET COLORS
122D	12	2	7/.0305	0.015	0.045	0.39	77	BLACK
124D	12	4	7/.0305	0.015	0.045	0.42	138	BLACK
142D	14	2	7/.0242	0.015	0.045	0.35	62	BLACK
144D	14	4	7/.0242	0.015	0.045	0.38	99	BLACK
162D	16	2	7/.0192	0.015	0.045	0.31	42	BLACK
164D	16	4	7/.0192	0.015	0.045	0.34	69	BLACK
184D	18	4	7/26	0.015	0.045	0.31	45	BLACK
184DS(OAS)*	18	4	7/26	0.015	0.045	0.31	52	BLACK
186D	18	6	7/26	0.015	0.045	0.36	72	BLACK
188D	18	8	7/26	0.015	0.045	0.38	89	BLACK
222PDS(OAS)*	22	2	7/30	0.010	0.032	0.23	25	BLACK
222PDES(EPS)**	22	4	SOLID	0.010	0.032	0.165	24	BLACK

AVAILABLE ON REELS

*OAS: OVERALL SHIELD

**EPS: EACH PAIR SHIELDED

While Signature Wire Corp. has made every reasonable effort to ensure the accuracy of these specifications, information contained herein may be subject to error and omission and to change without notice. Signature Wire Corp. provides these specifications on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied.