

FIBER OPTIC CABLE PLENUM
2 FIBER MULTIMODE

REV. 0 10/24/2006



PART NUMBER: F2MMMR

DESCRIPTION: 2 FIBER, 62.5/125 MULTIMODE FIBER, TIGHT-BUFFERED, PLENUM

PHYSICAL CHARACTERISTICS:

FIBER SIZE (CORE/CLADDING): 62.5/1.25/900 Micron
FIBER COUNT: 2
PLENUM: YES
TIGHT BUFFERED: YES
LOOSE TUBE: NO
OUTSIDE DIAMETER: .11 X .22"
JACKET MATERIAL & THICKNESS: PVC/1.6mm
JACKET COLOR: ORANGE
RIPCORD: YES
MAXIMUM LOAD (INSTALLATION): 150 LBS
MINIMUM BEND RADIUS (INSTALLATION): 2.0"
PACKAGING: REELS
SHIPPING WEIGHT:

OPTICAL CHARACTERISTICS:

MINIMUM BANDWIDTH 850/1300nm: 160/500MHz-km
MAX. ATTENUATION 850/1300nm: 3.75/1.5 db/km

UL CRITERIA:

UL TYPE OR STYLE: OFCP
FLAME RESISTANCE:

NOTES:

1. While Signature Wire Corp. has made every reasonable effort to ensure the accuracy of these specifications, information contained herein may be subject to error and omission and to change without notice. Signature Wire Corp. provides these specifications on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied.