

FIBER OPTIC CABLE
12 FIBER MULTIMODE

REV. 0 10/24/2006



PART NUMBER: **F12MMR**

DESCRIPTION: *12 FIBER, 62.5/125 MULTIMODE FIBER, TIGHT-BUFFERED, PVC, SUITABLE FOR INDOOR USE.*

PHYSICAL CHARACTERISTICS:

FIBER SIZE (CORE/CLADDING): 62.5/1.25/900 Micron
FIBER COUNT: 12
PLENUM: NO
TIGHT BUFFERED: YES
LOOSE TUBE: NO
OUTSIDE DIAMETER: .225"
JACKET MATERIAL & THICKNESS: PVC/1.6mm
JACKET COLOR: ORANGE
RIPCORD: YES
MAXIMUM LOAD (INSTALLATION): 300 LBS
MINIMUM BEND RADIUS (INSTALLATION): 3.8"
PACKAGING: REELS
SHIPPING WEIGHT: 20 LBS/1000'

OPTICAL CHARACTERISTICS:

MINIMUM BANDWIDTH 850/1300nm: 200/500 MHz-km
MAX. ATTENUATION 850/1300nm: 3.25/1.25 db/km

UL CRITERIA:

UL TYPE OR STYLE: OFCR
FLAME RESISTANCE:

NOTES:

1. While Signature Wire Corp. has made every reasonable effort to ensure the accuracy of these specifications, information contained herein may be subject to error and omission and to change without notice. Signature Wire Corp. provides these specifications on an "AS IS" basis, with no representations or warranties, whether expressed, statutory or implied.