

MULTI-CONDUCTOR CABLES - UNSHIELDED
 12 TO 22 AWG 2C TO 6C STRANDED BC OR SOLID BC

7/5/08 REV 1.1



CONDUCTORS: STRANDED OR SOLID BARE COPPER
INSULATION: PVC
JACKET: PVC
TEMPERATURE RATING: -20 TO +60 DEG C
OPERATING VOLTAGE: 300V
UL TYPE OR STYLE: CM, CMR AND/OR CL3

COLOR CODE CHART:

CONDUCTOR	COLOR	CONDUCTOR	COLOR	CONDUCTOR	COLOR
1ST	BLACK	5TH	BROWN	9TH	PURPLE
2ND	RED	6TH	BLUE	10TH	GRAY
3RD	WHITE	7TH	ORANGE	11TH	PINK
4TH	GREEN	8TH	YELLOW	12TH	TAN

PART NO	AWG	NUMBER OF CONDUCTORS	STRAND	NOM INSULATION THICKNESS (INCHES)	NOM JACKET THICKNESS (INCHES)	NOM OD (INCHES)	WEIGHT (LBS.) PER 1000'	JACKET COLORS
122	12	2	19/25	0.010	0.028	0.296	68	GRAY
162	16	2	19/29	0.010	0.022	0.198	30	GRAY
182	18	2	7/26	0.010	0.020	0.172	20	GRAY
183	18	3	7/26	0.010	0.022	0.187	30	GRAY
184	18	4	7/26	0.010	0.022	0.203	37	GRAY
222	22	2	7/30	0.007	0.016	0.120	11	GRAY, WHITE
224	22	4	7/30	0.007	0.014	0.126	15	GRAY, WHITE
222SS	22	2	SOLID	0.009	0.016	0.120	9	GRAY, WHITE
224SS	22	4	SOLID	0.009	0.018	0.149	15	GRAY, WHITE
226	22	6	7/30	0.007	0.022	0.170	24	GRAY, WHITE
226SS	22	6	SOLID	0.009	0.022	0.170	24	GRAY

REELS AND/OR E-Z PULL BOXES

While Signature Wire Corp. has made every reasonable effort to ensure the accuracy of these specifications, information contained herein may be subject to error and

MULTI-CONDUCTOR CABLES - UNSHIELDED
12 TO 22 AWG 2C TO 6C STRANDED BC OR SOLID BC

7/5/08 REV 1.1

omission and to change without notice. Signature Wire Corp. provides these specifications on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied.