

MULTI-CONDUCTOR PLENUM CABLES - UNSHIELDED
12 TO 22 AWG 2C TO 6C STRANDED BC

7/5/08 REV 1.0



CONDUCTORS: STRANDED BARE COPPER
INSULATION: LOW SMOKE PVC
JACKET: LOW SMOKE PVC WITH RIPCORD
TEMPERATURE RATING: -20 TO +75 DEG C
OPERATING VOLTAGE: 300V
UL TYPE OR STYLE: CMP AND/OR CL3P

COLOR CODE CHART:

CONDUCTOR	COLOR	CONDUCTOR	COLOR	CONDUCTOR	COLOR
1ST	BLACK	5TH	BROWN	9TH	PURPLE
2ND	RED	6TH	BLUE	10TH	GRAY
3RD	WHITE	7TH	ORANGE	11TH	PINK
4TH	GREEN	8TH	YELLOW	12TH	TAN

PART NO	AWG	NUMBER OF CONDUCTORS	STRAND	NOM INSULATION THICKNESS (INCHES)	NOM JACKET THICKNESS (INCHES)	NOM OD (INCHES)	WEIGHT (LBS.) PER 1000'	JACKET COLORS
122M	12	2	19/25	0.0085	0.018	0.256	54	WHITE
124M	12	4	19/25	0.009	0.018	0.318	114	WHITE
142M	14	2	19/27	0.009	0.020	0.216	38	WHITE
144M	14	4	19/27	0.009	0.020	0.274	72	WHITE
162M	16	2	19/29	0.008	0.020	0.188	27	WHITE
164M	16	4	19/29	0.008	0.020	0.219	47	WHITE
182M	18	2	7/26	0.007	0.016	0.150	17	WHITE
184M	18	4	7/26	0.007	0.020	0.183	32	WHITE
222M	22	2	7/30	0.006	0.016	0.114	8	WHITE
224M	22	4	7/30	0.006	0.016	0.131	14	WHITE
226M	22	6	7/30	0.006	0.020	0.155	20	WHITE

REELS

While Signature Wire Corp. has made every reasonable effort to ensure the accuracy of these specifications, information contained herein may be subject to error and omission and to change without notice. Signature Wire Corp. provides these specifications on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied.